

Jyoti Polycontainers Pvt. Ltd.

Works/ Office: R - 554/555, T.T.C., M.I.D.C., Near Golden Garage, Rabale, Navi Mumbai - 400 701, Maharashtra, India. I **Tel:** +91 22 2764 1694

Email: info@jypolycontainer.com | Website: www.jypolycontainer.com



Item	500 ML (Pesticide)
Construction of Material	HM-HDPE
Capacity	500 ML
Capacity Brimful	600 ML
Height	176 mm
Diameter	76 mm
ID	18 mm
Tare Weight	65 Gms

Testing Parameters	
Leakage Test	Water filled article will be kept horizontally for 1 hour & no leakage should be observed.
Drop Test	When article filled with water & dropped from 1.2 mtrs. It should not break.
Stack Test (1+5)	The stacking test is done in a UTM machine where the load of 5 drums is put on 1 drum for 1 hour and it should not bulge.

UN Approval: We can avail the same as per your requirement.
Colour available: Blue, Red, Yellow, Green as per client's request.
Marking: Will be screen printed as per client's specifications.

Disclaimer: - This product information sheet is provided for general information purpose only. Jyoti Polycontainers Pvt. Ltd. products require thorough testing by the customer to verify the suitability for the application. Jyoti Polycontainers Pvt. Ltd assumes no liability for the use of the content of this product information or the applications of its products. Jyoti Polycontainers Pvt. Ltd. reserves the rights to change the product information sheet from time to time.