

Jyoti Global Plast Limited.

Work/Office: R – 554/555, T.T.C., M.I.D.C., Near Golden Garage. Rabale, Navi Mumbai – 400701, Maharashtra, India. Mob No.: 8591585497 **Email ID:** info@jyotiglobalplast.com | **Website:** www.jyotiglobalplast.com



Item	20 LTR Ribbed (Polycan)
Construction of Material	HM-HDPE
Capacity	20 Liters
Capacity Brimful	22.4 Liters
Height	405 mm
Width	248 mm
Length	260 mm
Mouth Diameter	56.5 mm
Tare Weight	1.3 Kg TO 1.6 Kg

Testing Parameters		
Leakage Test	Water filled article will be kept horizontally for 1 hour & no leakage should be observed.	
Drop Test	When article filled with water & dropped from 1.2 mtrs. It should not break.	
Stack Test (1+5)	The stacking test is done in a UTM machine where the load of 5 drums is put on 1 drum for 1 hour and it should not bulge.	

UN Approval	: We can avail the same as per your requirement.
Colour available	: Blue, Red, Yellow, Green as per client's request.
Marking	: Will be screen printed as per client's specifications.

Disclaimer: - This product information sheet is provided for general information purpose only. Jyoti Global Plast Limited., products require through testing by the customer to verify the suitability for the application. Jyoti Global Plast Limited., assumes no liability for the use of the content of this product information or the applications of its products. Jyoti Global Plast Limited., reserves the rights to change the product information sheet from time to time.