



Jyoti Global Plast Limited.

Work/Office: R – 554/555, T.T.C., M.I.D.C., Near Golden Garage.

Rabale, Navi Mumbai – 400701, Maharashtra, India.

Mob No.: 8591585497

Email ID: info@jyotiglobalplast.com | Website: www.jyotiglobalplast.com



Item	50 LTR RKT (Round N/M)
Construction of Material	HM-HDPE
Capacity	50 Liters
Capacity Brimful	58.3 Liters
Height	567 mm
Width	325 mm
Length	390 mm
Mouth Diameter	60 mm
Tare Weight	2.3 Kg TO 2.8 Kg

Testing Parameters	
Leakage Test	Water filled article will be kept horizontally for 1 hour & no leakage should be observed.
Drop Test	When article filled with water / sand is dropped from 1.2 mtrs. It should not break.
Stack Test (1 + 2)	The stacking test is done in a UTM machine where the load of 2 drums is put on 1 drum for 1 hour and it's should not bulge.

UN Approval : We can avail the same as per your requirement.

Colour available : Blue, Red, Yellow, Green as per client's request.

Marking : Will be screen printed as per client's specifications.

Disclaimer: - This product information sheet is provided for general information purpose only. Jyoti Global Plast Limited., products require through testing by the customer to verify the suitability for the application. Jyoti Global Plast Limited., assumes no liability for the use of the content of this product information or the applications of its products. Jyoti Global Plast Limited., reserves the rights to change the product information sheet from time to time.