



Jyoti Global Plast Limited.

Work/Office: R – 554/555, T.T.C., M.I.D.C., Near Golden Garage.

Rabale, Navi Mumbai – 400701, Maharashtra, India.

Mob No.: 8591585497

Email ID: info@jyotiglobalplast.com | Website: www.jyotiglobalplast.com



Item	500 ML (Dotted)
Construction of Material	HM-HDPE
Capacity	500 ML
Capacity Brimful	545 ML
Height	175 mm
Length	94 mm
Width	48 mm
ID	30 mm
Tare Weight	65 Gms

Testing Parameters	
Leakage Test	Water filled article will be kept horizontally for 1 hour & no leakage should be observed.
Drop Test	When article filled with water & dropped from 1.2 mtrs. It should not break.
Stack Test (1 + 5)	The stacking test is done in a UTM machine where the Load of 5 drums is put on 1 drum for 1 hour and it should not bulge.

UN Approval : We can avail the same as per your requirement.

Colour available : Blue, Red, Yellow, Green as per client's request.

Marking : Will be screen printed as per client's specifications.

Disclaimer : - This product information sheet is provided for general information purpose only. Jyoti Global Plast Limited., products require thorough testing by the customer to verify the suitability for the application. Jyoti Global Plast Limited., assumes no liability for the use of the content of this product information or the applications of its products. Jyoti Global Plast Limited., reserves the rights to change the product information sheet from time to time.